

The GH-Method

Viscoelastic or Viscoplastic Glucose Theory (VGT #110): Two CVD Case Studies Applying Three Tools of Viscoelasticity and Viscoplasticity Theory of Space Domain, Wave Theory of Time Domain, and Fourier Transform of Frequency Domain to Investigate Three Different Energies Associated with Cardiovascular Disease Risk % versus Daily Estimated Average Glucose and Body Weight for 6 Years from Y2017 to Y2022 and 11 Years from Y2012 to Y2022 Based on GH-Method: Math-Physical Medicine (No. 700)

Gerald C. Hsu*

eclaireMD Foundation, USA

Keywords: Viscoelastic; Viscoplastic; Cardiovascular disease; Carbohydrates; Sugar; Walking k-steps; Postprandial plasma glucose; Fasting plasma glucose; Type 2 diabetes; Fast Fourier transform

Abbreviations: CVD: cardiovascular disease; FFT: fast Fourier transform; T2D: type 2 diabetes; PPG: postprandial plasma glucose; FPG: fasting plasma glucose; FD: frequency domain; SD: space domain; TD: time domain; MPM: math-physical medicine

1. INTRODUCTION

The author is an engineer who has conducted medical research work over the past 13 years in the fields of endocrinology, metabolic disorder-induced chronic diseases (especially diabetes), and their resulting various medical complications, including cardiovascular disease (CVD) and stroke. Thus far, he has written and published nearly 700 research papers in 100+ medical journals using his developed math-physical medicine methodology (MPM).

Beginning with Paper No. 578 dated 1/8/2022, he has written 100+ medical papers using viscoelasticity and viscoplasticity theories (VGT) tools from physics and engineering disciplines. These papers aim to explore some hidden physical behaviors and provide a deeper quantitative understanding of the inter-relationships of a selected output (symptom) versus singular input or multiple

inputs (root causes, risk factors, or influential factors).

In the medical research field, the hidden biophysical behaviors and possible inter-relationships exist among lifestyle details, medical conditions, chronic diseases, and certain medical complications, such as heart attacks, stroke, cancers, dementia, and even longevity concerns. He has noticed that most medical subjects with their associated data, multiple symptoms, and influential factors are “time-dependent” which means that all biomedical variables change from time to time because living cells of the human body are both organic and dynamically changing. This is what Professor Norman Jones, the author’s adviser at MIT, suggested to him in December 2021 and why he utilizes the VGT tools in physics and engineering to conduct his medical research work since then.

The author would like to describe the essence of the VGT methodology in 6 simple steps in

plain English instead of mathematical equations. For readers who do not have an extensive academic background in engineering, physics & mathematics, an excerpt of VGT from Wikipedia is included in the Method section of this full-text article.

The first step is to collect the output or symptom data (strain or ϵ) within a selected time window, e.g. the cardiovascular disease (CVD) risk %. The second step is to calculate the output change rate with time ($d\epsilon/DT$), e.g. the change rate of CVD risk over each year. The third step is to collect the input data or cause (viscosity or η) within the same time window, e.g. daily estimated average glucose (eAG) and body weight (BW) in the morning. The fourth step is to calculate the time-dependent “stress or σ by multiplying $d\epsilon/dt$ and η together. The “time-dependent input equation” is “stress $\sigma =$ strain change rate of $d\epsilon/DT *$ viscosity η ”. The fifth step is to plot the input-output (i.e. stress-strain or cause-symptom) curve in a 2-dimensional space-domain or SD (x-axis versus y-axis) with strain (output or symptom) on the x-axis and stresses (time-dependent inputs or causes) on the y-axis. The sixth step is to calculate the total enclosed area, using the trapezoid formula, within these input-output curves (or hysteresis loop areas), which is also the indicator of associated energies (either created energy or dissipated energy during the loading and unloading process) of this input and output dataset. These energy values can also be considered as the degrees of influence on output (symptom) by various inputs (causes).

After providing this language-based description, he would like to use the defined VGT equations to address the unique “time-dependency characteristics” and their quantitative approach to engineering and medical variables as follows:

Strain

= ϵ

= individual strain or symptom value at the present time duration

Stress

= σ (based on the change rate of strain or symptom multiplying with a chosen viscosity factor η or cause)

= $\eta * (d\epsilon/dt)$

= $\eta * (d\text{-strain}/d\text{-time})$

= (viscosity factor or cause η using individual viscosity factor or cause at present time duration) * (strain or symptom at present quarter - strain or symptom at previous time duration)

Some of these inputs (causes or viscosity factors) are further normalized by dividing them by a certain established health standard, such as 120 mg/dL for eAG, and 170 lbs. for his ideal body weight. Using non-normalized and originally collected data would distort the numerical comparison result of the SD-hysteresis loop areas. The normalization process can remove the dependency of the individual unit or certain unique characteristics associated with each viscosity factor. This process allows him to convert these originally collected biomarkers into a set of “dimensionless biomarkers” for easier numerical comparison and result interpretation.

In addition, the author decided to utilize a frequency-domain (FD) fast Fourier transform (FFT) energy analysis method on the same dataset - CVD risk % versus eAG and BW. In this particular report, he has chosen one newly defined variable for FD-FFT analysis for comparison against the SD-VGT analysis.

The FD case uses a newly defined variable of (strain*stress) which includes a somewhat “amplified behavior” from both causes and symptom. For this study, these newly defined variables are $CVD*(CVD \text{ rate}*eAG)$ and $CVD*(CVD \text{ rate}*BW)$.

He then inserts this newly defined variable of strain*stress from an SD into a TD to perform an FFT operation to generate a frequency curve in FD. The Y-axis values of FD are related to the individual FD-FFT energies and the X-axis values are individual frequencies. A brief excerpt of “TD to FD via FFT” from Wikipedia is also included in the methods section.

2. METHODS

2.1 The author’s case of obesity, type 2 diabetes (T2D), and 5 cardiac episodes

The author has been a severe T2D patient since 1996. He weighed 220 lb. (100 kg, BMI 32.5) at that time. By 2010, he still weighed 198 lb. (BMI 29.2) with average daily glucose

of 250 mg/dL to 280 mg/dL (HbA1C of 10% to 11%). During that year, his triglycerides reached 1161 (normal level <150) and his albumin-creatinine ratio (ACR) at 116 (normal level <30). He also suffered from five cardiac episodes within a decade. In 2010, three independent physicians warned him regarding his need for kidney dialysis treatment and his future high risk of dying from his severe diabetic complications. Other than the cerebrovascular disease (stroke), he has suffered many diabetic complications, including issues associated with macrovascular in the heart and brain and microvascular in the kidneys, bladder, retina, as well as nerves.

In 2010, he decided to launch his self-study on endocrinology, diabetes, and food nutrition to save his own life. During 2015 and 2016, he developed four prediction models related to diabetes conditions: weight, postprandial plasma glucose (PPG), fasting plasma glucose (FPG), and HbA1C. As a result, from using his developed mathematical metabolism index (MI) model in 2014 and these four biomarker prediction tools, by end of 2016, his weight was reduced from 220 lbs. (100 kg, BMI 32.5) to 176 lbs. (89 kg, BMI 26.0), waistline from 44 inches (112 cm) to 33 inches (84 cm), average finger glucose reading from 250 mg/dL to 120 mg/dL, and lab-tested A1C from 10% to ~6.5%. One of his major health accomplishments is that he no longer takes any diabetes medications as of 12/8/2015.

In 2017, he has achieved excellent results on all fronts, especially glucose control. However, during the pre-COVID period of 2018 and 2019, he traveled to approximately 50+ international cities to attend 65+ medical conferences and made ~120 oral presentations. This hectic schedule inflicted damage to his diabetes control, through dining out frequently, post-meal exercise disruption, jet lag, unwanted stress, and along with the overall metabolic impact due to his irregular life patterns through a busy travel schedule; therefore, his glucose control and overall metabolism state were somewhat affected during this two-year heavier traveling period. The health impact of his lifestyle during 2018-2019 can be seen clearly from his collected biomarkers.

Since 2020, living in a COVID-19 quarantined lifestyle, not only has he published 400+ medical papers in 100+

journals, but he has also reached his best health conditions in the past 27 years. By the beginning of 2022, his weight was further reduced to 168 lbs. (BMI 24.8) along with a 5.8% A1C value (beginning level of pre-diabetes), without having any medication interventions or insulin injections. These good results are due to his non-traveling, low-stress, sound sleep at night, and regular daily life routines. Of course, his knowledge of chronic diseases, practical lifestyle management experiences, and development of various high-tech tools contribute to his excellent health status since 1/19/2020, the beginning date of his COVID-19 self-quarantined life.

On 5/5/2018, he applied a continuous glucose monitoring (CGM) sensor device on his upper arm and checks his glucose measurements every 5 minutes for a total of ~288 times each day. He has maintained the same measurement pattern to the present day. In his research work, he uses his CGM sensor glucose at a time interval of 15 minutes (96 data per day). Incidentally, the difference in average sensor glucoses between 5-minute intervals and 15-minute intervals is only 0.7% (average glucose of 112.15 mg/dL for 5 minutes and average glucose of 111.33 mg/dL for 15 minutes with a correlation of 96% between these two sensor glucose curves) during the period from 2/19/20- to 5/9/22.

Therefore, over the past 13 years, he could study and analyze the collected and processed 3+ million data regarding his health status, medical conditions, and lifestyle details. He applies his knowledge, models, and tools from mathematics, physics, engineering, and computer science to conduct his medical research work. His research is based on the aims of achieving both “high precision” with “quantitative proof” findings in the arena of preventive medicine.

The following timetable provides a rough sketch of the emphasis in his medical research during each stage:

2000-2013: Self-study diabetes and food nutrition, developing a data collection and analysis software.

2014: Develop a mathematical model of metabolism, using engineering modeling and advanced mathematics.

2015: Weight & FPG prediction models, using neuroscience.

2016: PPG & HbA1C prediction models, using optical physics, artificial intelligence (AI), and neuroscience.

2017: Complications due to macro-vascular research, such as cardiovascular disease (CVD), coronary heart diseases (CHD), and stroke, using pattern analysis and segmentation analysis.

2018: Complications due to micro-vascular research such as kidney (CKD), bladder, foot, retina issues (DR), and neuropathy.

2019: CGM big data analysis, using wave theory, energy theory, frequency domain analysis, quantum mechanics, and AI.

2020: Cancer, dementia, longevity, geriatrics, DR, hypothyroidism, diabetic foot, diabetic fungal infection, and linkage between metabolism and immunity, learning about certain infectious diseases, such as COVID-19.

2021: Applications of linear elastic glucose theory (LEGT) and perturbation theory from quantum mechanics on medical research subjects, such as chronic diseases and their complications, cancer, and dementia.

2022: Applications of viscoelastic/viscoplastic glucose theory (LEGT) on 100+ biomedical research cases.

Again, to date, he has read ~3,000 published medical papers and spent around 40,000 hours self-studying and researching medicine. He has collected and calculated more than three million pieces of data regarding his medical conditions and lifestyle details. In addition, he has written ~700 medical research notes and published 600+ papers in 100+ various medical and engineering journals, including 7 special editions. Moreover, he has also given ~120 presentations at ~65 international medical conferences. He has continuously dedicated his time (11-12 hours per day and work each day of a year, without rest) and efforts to his medical research work and shared his findings and learnings with other patients worldwide.

2.2 MPM background

To learn more about his developed GH-Method: math-physical medicine or MPM methodology, readers can select the following three articles from the 400+ published medical papers.

The first paper, No. 386, describes his MPM methodology in a general conceptual format. The second paper, No. 387, outlines the history of his personalized diabetes research, various application tools, and the differences between the biochemical medicine (BCM) approach versus the MPM approach. The third paper, No. 397, depicts a general flow diagram containing ~10 key MPM research methods and different tools.

All of the listed papers in the Reference section are his written and published medical research papers.

2.3 Elasticity, plasticity, viscoelasticity, and viscoplasticity (LEGT & VGT)

The difference between elastic materials and viscoelastic materials (from “Soborthans, innovating shock and vibration solutions”).

What are elastic materials?

Elasticity is the tendency of solid materials to return to their original shape after forces are applied on them. When the forces are removed, the object will return to its initial shape and size if the material is elastic.

Medical analogy: The medical application is when cause or risk factors are reduced or removed, the symptoms of certain disease would be improved or ceased.

What are viscous materials?

Viscosity is a measure of a fluid’s resistance to flow. A fluid with large viscosity resists motion. A fluid with low viscosity flows. For example, water flows more easily than syrup because it has a lower viscosity. High viscosity materials might include honey, syrups, or gels – generally things that resist flow. Water is a low viscosity material, as it flows readily. Viscous materials are thick or sticky or adhesive. Since heating reduces viscosity, these materials don’t flow easily. For example, warm syrup flows more easily than cold.

What is viscoelastic?

Viscoelasticity is the property of materials that exhibit both viscous and elastic characteristics when undergoing deformation. Synthetic polymers, wood, and human tissue, as well as metals at high temperature, display significant viscoelastic effects. In some applications, even a small viscoelastic response can be significant.

Medical analogy: Viscoelastic behavior means material has “time-dependent” characters. Biomedical data, i.e. biomarkers, are time-dependent due to body cells are organic which changes with time constantly.

Elastic behavior versus viscoelastic behavior

The difference between elastic materials and viscoelastic materials is that viscoelastic materials have a viscosity factor and the elastic ones don't. Because viscoelastic materials have the viscosity factor, they have a strain rate dependent on time. Purely elastic materials do not dissipate energy (heat) when a load is applied, then removed; however, a viscoelastic substance does.

Medical analogy: Most of the biomarkers display time-dependency; therefore, they have both change-rate of time and viscosity factor behaviors. Viscoelastic biomarkers do dissipate energy when a causing force is applied to them.

The following brief introductions are excerpts from Wikipedia:

“Elasticity (physics):

The physical property is when materials or objects return to their original shape after deformation.

In physics and materials science, elasticity is the ability of a body to resist a distorting influence and to return to its original size and shape when that influence or force is removed. Solid objects will deform when adequate loads are applied to them; if the material is elastic, the object will return to its initial shape and size after removal. This is in contrast to plasticity, in which the object fails to do so and instead remains in its deformed state.

Hooke's law states that the force required to deform elastic objects should be directly proportional to the distance of deformation, regardless of how large that distance becomes. This is known as perfect elasticity, in which a given object will return to its original shape no matter how strongly it is deformed. This is an ideal concept only; most materials that possess elasticity in practice remain purely elastic only up to very small deformations, after which plastic (permanent) deformation occurs.


In engineering, the elasticity of a material is quantified by the elastic modulus such as the Young's modulus, bulk modulus or shear modulus which measure the amount of stress needed to achieve a unit of strain; a higher modulus indicates that the material is harder to deform. The material's elastic limit or yield strength is the maximum stress that can arise before the onset of plastic deformation.

Medical analogy: The elastic behavior analogy in medicine can be expressed by the metal rod analogy for the postprandial plasma glucose (PPG). Consuming carbohydrates and/or sugar acts like a tensile force to stretch a metal rod longer, while post-meal exercise acts like a compressive force to suppress a metal rod shorter. If lacking food consumption and exercise, the metal rod (analogy of PPG) will remain its original length, for a non-diabetes or less severe type 2 diabetes (T2D) patient.

Plasticity (physics):


Deformation of a solid material undergoing non-reversible changes of shape in response to applied forces.

In physics and materials science, plasticity, also known as plastic deformation, is the ability of a solid material to undergo permanent deformation, a non-reversible change of shape in response to applied forces. For example, a solid piece of metal being bent or pounded into a new shape displays plasticity as permanent changes occur within the material itself. In engineering, the transition from elastic behavior to plastic behavior is known as yielding. Plastic deformation is observed in most materials, particularly metals, soils, rocks, concrete, and foams.



A stress-strain curve showing typical yield behavior for nonferrous alloys.

1. True elastic limit
2. Proportionality limit
3. Elastic limit
4. Offset yield strength



A stress-strain is typical of structural steel.

- 1: Ultimate strength
- 2: Yield strength (yield point)
- 3: Rupture
- 4: Strain hardening region
- 5: Necking region
- A: Apparent stress (F/A0)
- B: Actual stress (F/A)

For many ductile metals, tensile loading applied to a sample will cause it to behave in an elastic manner. Each increment of load is accompanied by a proportional increment in extension. When the load is removed, the piece returns to its original size. However, once the load exceeds a threshold – the yield strength – the extension increases more rapidly than in the elastic region; now when the load is removed, some degree of extension will remain.

Medical analogy: A plastic behavior analogy in medicine is the PPG level of a severe T2D patient. Even consuming a smaller amount of carbs/sugar, the patient’s PPG will rise sharply which cannot be totally brought down to a healthy PPG level even with a significant amount of exercise. This means the PPG level has exceeded its “elastic limit” and entering into a “plastic range”.

Viscoelasticity:

Property of materials with both viscous and elastic characteristics under deformation.

In materials science and continuum mechanics, viscoelasticity is the property of materials that exhibit both viscous and elastic characteristics when undergoing deformation. Viscous materials, like water, resist shear flow and strain linearly with time when a stress is applied. Elastic materials strain when stretched and immediately return to their original state once the stress is removed.

Viscoelastic materials have elements of both of these properties and, as such, exhibit time-dependent strain. Whereas elasticity is usually the result of bond stretching along crystallographic planes in an ordered solid, viscosity is the result of the diffusion of atoms or molecules inside an amorphous material.

In the nineteenth century, physicists such as Maxwell, Boltzmann, and Kelvin researched and experimented with creep and recovery of glasses, metals, and rubbers. Viscoelasticity was further examined in the late twentieth century when synthetic polymers were engineered and used in a variety of applications. Viscoelasticity calculations depend heavily on the viscosity variable, η . The inverse of η is also known as fluidity, ϕ . The value of either can be derived as a function of temperature or as a given value (i.e. for a dashpot).


Depending on the change of strain rate versus stress inside a material, the viscosity can be categorized as having a linear, non-linear, or plastic response. In addition, when the stress is independent of this strain rate, the material exhibits plastic deformation. Many viscoelastic materials exhibit rubber-like behaviors explained by the thermodynamic theory of polymer elasticity.

Cracking occurs when the strain is applied quickly and outside of the elastic limit. Ligaments and tendons are viscoelastic, so the extent of the potential damage to them depends both on the rate of the change of their length as well as on the force applied.

A viscoelastic material has the following properties:

- hysteresis is seen in the stress-strain
- stress relaxation occurs: step constant strain causes decreasing stress
- creep occurs: step constant stress causes increasing strain
- its stiffness depends on the strain rate or the stress rate.

Elastic versus viscoelastic behavior:



Stress-strain curves for a purely elastic material (a) and a viscoelastic material (b). The red area is a hysteresis loop and shows the amount of energy lost (as heat) in a loading and unloading cycle. It is equal to $\oint \sigma d\epsilon$ where σ is stress and ϵ is strain. In other words, the hysteresis loop area represents the amount of energy during the loading and unloading process.

Unlike purely elastic substances, a viscoelastic substance has an elastic component and a viscous component. The viscosity of a viscoelastic substance gives the substance a strain rate dependence on time. Purely elastic materials do not dissipate energy (heat) when a load is applied, then removed. However, a viscoelastic substance dissipates energy when a load is applied, then removed. Hysteresis is observed in the stress-strain curve, with the area of the loop being equal to the energy lost during the loading cycle. Since viscosity is the resistance to thermally activated plastic deformation, a viscous material will lose energy through a loading cycle. Plastic deformation results in lost energy, which is uncharacteristic of a

purely elastic material's reaction to a loading cycle.

Viscoplasticity:

Viscoplasticity is a theory in continuum mechanics that describes the rate-dependent inelastic behavior of solids. Rate-dependence in this context means that the deformation of the material depends on the rate at which loads are applied. The inelastic behavior that is the subject of viscoplasticity is plastic deformation which means that the material undergoes unrecoverable deformations when a load level is reached. Rate-dependent plasticity is important for transient plasticity calculations. The main difference between rate-independent plastic and viscoplastic material models is that the latter exhibit not only permanent deformations after the application of loads but continue to undergo a creep flow as a function of time under the influence of the applied load.


Medical analogy: In viscoelastic or viscoplastic analysis, the stress component equals the strain change rate of time multiplying with the viscosity factor, or

$$\begin{aligned} \text{Stress } (\sigma) &= \text{strain } (\epsilon) \text{ change rate} * \text{viscosity factor } (\eta) \\ &= d\epsilon/dt * \eta \end{aligned}$$

$$\begin{aligned} \text{The hysteresis loop area} &= \text{the integrated area of stress } (\sigma) \text{ and strain } (\epsilon) \text{ curve} \\ &= \oint \sigma d\epsilon \end{aligned}$$

2.4 From time-domain to frequency domain via Fourier transform

In physics, electronics, control systems engineering, and statistics, the frequency domain refers to the analysis of mathematical functions or signals concerning frequency, rather than time.[1] Put simply, a time-domain graph shows how a signal changes over time, whereas a frequency-domain graph shows how much of the signal lies within each given frequency band over a range of frequencies. A frequency-domain representation can also include information on the phase shift that must be applied to each sinusoid to be able to recombine the frequency components to recover the original time signal.



The Fourier transform converts the function's time-domain representation, shown in red, to the function's frequency-domain representation, shown in blue. The component frequencies, spread across the frequency spectrum, are represented as peaks in the frequency domain.

A given function or signal can be converted between the time and frequency domains with a pair of mathematical operators called transforms. An example is the Fourier transform, which converts a time function into a complex-valued sum or integral of sine waves of different frequencies, with amplitudes and phases, each of which represents a frequency component. The "spectrum" of frequency components is the frequency-domain representation of the signal. The inverse Fourier transform converts the frequency-domain function back to the time-domain function. A spectrum analyzer is a tool commonly used to visualize electronic signals in the frequency domain.

Advantages

One of the main reasons for using a frequency-domain representation of a problem is to simplify the mathematical analysis. For mathematical systems governed by linear differential equations, a very important class of systems with many real-world applications, converting the description of the system from the time domain to a frequency domain converts the differential equations to algebraic equations, which are much easier to solve.

In addition, looking at a system from the point of view of frequency can often give an intuitive understanding of the qualitative behavior of the system, and a revealing scientific nomenclature has grown up to describe it, characterizing the behavior of physical systems to time-varying inputs

using terms such as bandwidth, frequency response, gain, phase shift, resonant frequencies, time constant, resonance width, damping factor, Q factor, harmonics, spectrum, power spectral density, eigenvalues, poles, and zeros.

An example of a field in which frequency-domain analysis gives a better understanding than the time domain is music; the theory of operation of musical instruments and the musical notation used to record and discuss pieces of music is implicitly based on the breaking down of complex sounds into their separate component frequencies (musical notes).

Magnitude and phase

In using the Laplace, Z-, or Fourier transforms, a signal is described by a complex function of frequency: the component of the signal at any given frequency is given by a complex number. The modulus of the number is the amplitude of that component, and the argument is the relative phase of the wave. For example, using the Fourier transform, a sound wave, such as human speech, can be broken down into its component tones of different frequencies, each represented by a sine wave of different amplitude and phase. The response of a system, as a function of frequency, can also be described by a complex function. In many applications, phase information is not important. By discarding the phase information, it is possible to simplify the information in a frequency-domain representation to generate a frequency spectrum or spectral density. A spectrum analyzer is a device that displays the spectrum, while the time-domain signal can be seen on an oscilloscope.

Types

Although "the" frequency domain is spoken of in the singular, there are several different mathematical transforms that are used to analyze time-domain functions and are referred to as "frequency domain" methods. These are the most common transforms and the fields in which they are used:

- Fourier series – periodic signals, oscillating systems.
- Fourier transform – aperiodic signals, transients.

- Laplace transform – electronic circuits and control systems.
- Z transform – discrete-time signals, digital signal processing.
- Wavelet transform — image analysis, data compression.

More generally, one can speak of the transform domain for any transform. The above transforms can be interpreted as capturing some form of frequency, and hence the transform domain is referred to as a frequency domain.

Discrete frequency domain

The Fourier transform of a periodic signal has energy only at a base frequency and its harmonics. Another way of saying this is that a periodic signal can be analyzed using a discrete frequency domain. Dually, a discrete-time signal gives rise to a periodic frequency spectrum. Combining these two, if we start with a time signal which is both discrete and periodic, we get a frequency spectrum which is also both discrete and periodic. This is the usual context for a discrete Fourier transform.

History of term

The use of the terms "frequency domain" and "time domain" arose in communication engineering in the 1950s and early 1960s, with "frequency domain" appearing in 1953. See time domain: the origin of the term for details.

Note: For a more detailed description, please refer to the “consolidated method” section which is given at the beginning of the special issue.

3. RESULTS

All of the following 5 figures are showing the comparison between a shatter “stabilized” period from Y2017 to Y2022 and a longer “complete” period from Y2012 to Y2022.

Figure 1 shows 2 data tables.

Figure 2 illustrates 2 TD-squared causes energy analysis results.

Figure 3 displays 2 SD-VGT strain-stress energy analysis results.

Figure 1: 2 data tables.




Figure 2: 2 TD-squared causes energy analysis results.




Figure 3: 2 SD-VGT strain-stress energy analysis results.

Figure 4 reflects 2 FD-FFT energy analysis results.



Figure 4: 2 newly defined variable of (strain*stress) of FD-FFT energy analysis results.

Figure 5 depicts 2 energy contribution comparisons of 3 domains and time-period energy distribution results.




Figure 5: 2 energy contribution comparison of 3 domains and different time-period energy distribution results.

4. CONCLUSION

In summary, there are 6 observations from the 3 energy analyses, TD-squared causes, SD-VGT strain-stress energy, and FD-FFT energy of CVD Risk % versus eAG and BW:

(1) From the TD analysis of the collected data in 11 years, the calculated correlations are CVD vs. eAG = 83%; CVD vs. BW = 93%. For

the collected data in 6 years, the calculated correlations are CVD vs. eAG = 88%; CVD vs. BW = 76%. More interestingly, using the “squared-cause” approach, the 11-year energy ratio is eAG 48% versus BW 52%, while the 6-year energy ratio is eAG 46% versus BW 54%. This conclusion is based on a rudimentary physics definition of wave energy theory that “the wave’s energy is directly proportional to the square of the amplitude of this wave”. Application of this basic physics description only deals with one waveform, e.g. input or cause wave, which does not include its influence on the output waveform or symptom waveform. From the two case studies, the conclusion of both diabetes (eAG) and obesity (BW) contribute to the risk of developing CVD episodes is evident.

(2) Researching the part of the variation of strain and stress from the SD-VGT results of 11 years, we see that his CVD risk % decreased from 86% in Y2013 to 50% in Y2022. His eAG started at 128 mg/dL in Y2012 to 135 mg/dL in Y2014 and then dropped to 104 mg/dL in Y2022. His BW started at 189 lbs. in Y2012 and decreased to 170 lbs. in Y2022. However, from the SD-VGT results of 6 years, we see that his CVD risk % decreased from 55% in Y2017, rose slightly to 57% in Y2019, and then reduced to 50% in Y2022. His eAG started at 117 mg/dL in Y2017 and then dropped to 104 mg/dL in Y2022. His BW started at 174 lbs. in Y2017 and decreased to 170 lbs. in Y2022. Generally speaking, all the 3 biomarkers, CVD risk, eAG, and BW are decreasing year after year for both 11-year and 6-year periods. It should also be pointed out that the strain (CVD risk) change rates establish the basic waveform patterns of the 2 stress-strain curves resulting from eAG & BW.

(3) Researching more into the stress-strain diagrams from the SD-VGT analysis results, the 2 stress-strain curves’ general waveform patterns are similar to each other due to their identical strain (CVD risk) change rates. However, the 2 different normalized viscosities, eAG & BW, decide the final magnitudes of the curve shapes and the area of hysteresis loops. The combination of strain and stress components affects the actual size of the hysteresis loop area or its associated energy level, i.e. the degree of influence of the stresses or causes on the strain or symptom. The conclusive observation from this stress-

strain diagram is that for the 11-year data, eAG has generated a slightly larger share of energy 300 (51%), followed by BW (obesity) of 285 (49%), while in the 6-year data, eAG has generated a slightly lower share of energy 16 (47%), followed by BW (obesity) of 18 (53%).

(4) The author extracted strain (symptom) and stress (causes) from SD to form two newly-defined variables of (strain*stresses) to draw them in a TD diagram. Then, conducting an FFT operation to convert them into a frequency curve in FD. For the 11 years, the FD-FFT energy ratio is eAG (53%) versus BW (47%), while for the 6 years, eAG (45%) versus BW (55%). Although the mathematical operations for SD-VGT and FD-FFT are different, their results are extremely close to each other. This is the beauty of physics where almost everything under the sun follows physics principles.

(5) After inserting the results from TD-squared biomarker energy, SD-VGT energy, and FD-FFT energy into a combined bar chart, we can see the comparison among the three sets of results. In all three sets of results for both cases, eAG and BW contribute almost equally to the CVD Risk (with small deviations). The math-physical analysis methods are capable of discovering many hidden biophysical characteristics from datasets, no matter how subtle they are. For example, using SD-VGT and FD-FFT tools, in the 11-year case, the eAG's contributions are slightly higher (2%-6%) than the BW's contributions; however, in the 6-year case, the eAG's contributions are slightly lower (6%-10%) than BW's contributions. This interesting observation is a result of his glucose condition being worse than his weight situation in the 11-year dataset (especially during Y2012-Y2016), but his hyperglycemic control is better than his obesity control in the 6-year dataset.

(6) The most remarkable finding from the SD-VGT energy study is the time-duration distribution results. By combining eAG and BW, for the 11-year case, the uncontrolled 4-year period from 2012-Y2015 contributes 85%, the controlled 4-year period from Y2016-Y2019 contributes 13%, and the quarantined lifestyle during the pandemic contained the best-controlled period of 2.5 years from Y2020-Y2022 contributes only 3%. However, for the 6-year case, the controlled period, i.e. 3 intermediate years of Y2017-

Y2019 contributes 48%, and the quarantined lifestyle during the pandemic contained the best-controlled period of 2.5 years from Y2020-Y2022 contributes only 52%.

Both the SD-VGT energy tool adopted from engineering and the FD-FFT energy tool from physics have yielded extremely similar results with interesting clues for both periods. They also provide some useful interpretations of biomedical results from this research work on CVD risk % resulting from eAG and BW. This particular article has further offered additional proof regarding the appropriate selection of the newly defined FD variable of (strain * stress).

5. ACKNOWLEDGMENT

Without Professor Norman Jones at MIT as his academic advisor, the author would not be able to conduct this particular research work and published 700 medical research papers. The author has never forgotten his advice to him that he should always focus on and enhance his basic strength in foundations, such as mathematics and physics, to make further improvements and advancements. Professor Jones has also provided him with a personal example of doing outstanding teaching and research job with an excellent work attitude, extreme focus and dedication, and ultimate commitment to advancing both science and engineering.

6. REFERENCES

For editing purposes, the majority of the references in this paper, which are self-references, have been removed for this article. Only references from other authors' published sources remain. The bibliography of the author's original self-references can be viewed at www.eclaircmd.com.

Readers may use this article as long as the work is properly cited, their use is educational and not for profit, and the author's original work is not altered.

To read additional published VGT analyses on medical research, please view them in the following three journals:

(1) Special Issue. The GH-Method. (<https://www.theghmethod.com>)

(2) Journal of Applied Material Science & Engineering Research (contact: Catherine)

(3) Advances in Bioengineering and Biomedical Science Research (contact: Sonny Hazi).

Viscoelastic and Viscoplastic Glucose Theory Application in Medicine

Gerald C. Hsu

